

Firestone PVC

Warranty Matrix

TABLE 1.01-1
Chart of Roofing System Applicability
Firestone PVC Membranes

System	Product	Slope	Barrel, Arch, etc.	Maximum Height	Maximum Warranty Term
Adhered	Firestone PVC .050" (1.3 mm)	Unlimited	OK	250' (76.2 m)	15-year
	Firestone PVC Minimum .050" (1.3 mm)	Unlimited	OK	250' (76.2 m)	15-year
	Firestone PVC .060" (1.5 mm)	Unlimited	OK	250' (76.2 m)	20-year
	Firestone PVC Minimum .060" (1.5 mm)	Unlimited	OK	250' (76.2 m)	20-year
	Firestone PVC .080" (2.0 mm)	Unlimited	OK	250' (76.2 m)	20-year
	Firestone PVC Minimum .080" (2.0 mm)	Unlimited	OK	250' (76.2 m)	20-year
	Firestone PVC XR .050" (1.3 mm)	Max. 4:12 (33.3%)	OK	250' (76.2 m)	15-year
	Firestone PVC XR .060" (1.5 mm)	Max. 4:12 (33.3%)	OK	250' (76.2 m)	20-year
	Firestone PVC XR Minimum .060" (1.5 mm)	Max. 4:12 (33.3%)	OK	250' (76.2 m)	20-year
	Firestone PVC XR .080" (2.0 mm)	Max. 4:12 (33.3%)	OK	250' (76.2 m)	20-year
	Firestone PVC XR Minimum .080" (2.0 mm)	Max. 4:12 (33.3%)	OK	250' (76.2 m)	20-year
Mechanically Attached	Firestone PVC or PVC XR .050" (1.3 mm)	Max. 4:12 (33.3%)	OK	120' (36.6 m)	15-year
	Firestone PVC or PVC XR .060" (1.5 mm)	Max. 4:12 (33.3%)	OK	120' (36.6 m)	20-year
	Firestone PVC or PVC XR Minimum .060" (1.5 mm)	Max. 4:12 (33.3%)	OK	120' (36.6 m)	20-year
	Firestone PVC or PVC XR .080" (2.0 mm)	Max 4:12	OK	120' (36.6 m)	20-year
	Firestone PVC or PVC XR Minimum .080" (2.0 mm)	Max 4:12	OK	120' (36.6 m)	20-year
InvisiWeld Plate Induction Bonded System	Firestone PVC .050" (1.3 mm)	Max. 4:12 (33.3%)	OK	120' (36.6 m)	15-year
	Firestone PVC Minimum .050" (1.3 mm)	Max. 4:12 (33.3%)	OK	120' (36.6 m)	15-year
	Firestone PVC .060" (1.5 mm)	Max. 4:12 (33.3%)	OK	120' (36.6 m)	20-year
	Firestone PVC Minimum .060" (1.5 mm)	Max. 4:12 (33.3%)	OK	120' (36.6 m)	20-year
	Firestone PVC .080" (2.0 mm)	Max. 4:12 (33.3%)	OK	120' (36.6 m)	20-year
	Firestone PVC Minimum .080" (2.0 mm)	Max. 4:12 (33.3%)	OK	120' (36.6 m)	20-year