

PRIMER QUICK REFERENCE GUIDE

| | RubberGard EPDM | | | | | UltraPly TPO | | | | Underlayments ² | | | | Temperature (°F) | | Coverage (SF/gal) Single Sided | Shelf Life | VOC Content |
|---------------------------------|-----------------|------------------------|----------|-----|----------------|--------------|---------------------|--------------|--------|----------------------------|-----------|---------|-------------|------------------|-------------|--------------------------------------|------------|-------------|
| | LS-FR/FR | FullForce ¹ | Platinum | MAX | EcoWhite/Plat | UltraPly TPO | TPO SA ¹ | Flex/Adhered | TPO XR | V-Force | Clad-Gard | Enverge | BASEGARD SA | Storage | Application | | | |
| QuickPrime Plus | Y | Y | Y | Y | Y ⁵ | | | | | | | | | 60-80 | 40 | 200-250 | 1 year | <=664 g/L |
| QuickPrime Plus LVOC | Y | Y | Y | Y | Y ⁵ | | | | | | | | | 60-80 | 40 | 150-225 | 1 year | <=250 g/L |
| Single-Ply QuickPrime | Y | Y | Y | Y | Y | Y | Y | Y | | | | | | 60-80 | 40 | 200-250 | 1 year | 645 g/L |
| Single-Ply LVOC | Y | Y | Y | Y | Y | Y | Y | Y | | | | | | 60-80 | 40 | 200-250 | 1 year | <=250 g/L |
| Firestone SA Solvent Based (SB) | | | | | | | | | Y | Y | Y | | | 32-104 | 14+ | 80-133 | 2 years | 500 g/L |
| Firestone SA Water Based (WB) | | | | | | | | | Y | Y | Y | | | 41-105 | 41+ | 133-400 ⁴ | 2 years | 3 g/L |
| SA-LVOC Primer | | | | | | | | | Y | Y | Y | | | 32-104 | 14+ | 100-200 | 5 years | 240 g/L |
| SA Primer ³ | | | | | | | | | | | | Y | | 60-80 | 40 | 100-125 | 1 year | 664 g/L |

¹ A primer MUST be used for vertical applications. Primers can be brush or roll applied for VERTICAL applications only.

² Brush or roller application of primers for underlayments is acceptable.

³ Roller applicatoin only.

⁴ For use on Porous substrates only.

⁵ Can be used, but will leave a visual residue. Recommend using a Single-Ply Primer

