

Safety Data Sheet

Firestone Building Products Company

Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier

Product Name • All Purpose Bonding Adhesive LVOC

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified use(s) • Construction

1.3 Details of the supplier of the safety data sheet

Manufacturer • Firestone Building Products Company

200 4th Avenue S
Nashville, TN 37201-2208
United States

firestonemsds@bfdp.com

Telephone (General) • 800-428-4442

1.4 Emergency telephone number

Manufacturer • (800) 424-9300 - CHEMTREC

Manufacturer • (703) 527-3887 - CHEMTREC - International

Section 2: Hazards Identification

EU/EEC

According to: Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010]

According to: EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

2.1 Classification of the substance or mixture

CLP

- Flammable Liquids 2 - H225
- Skin Irritation 2 - H315
- Eye Irritation 2 - H319
- Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects - H336
- Reproductive Toxicity 2 - H361d
- Specific Target Organ Toxicity Repeated Exposure 2 - H373
- EUH066

DSD/DPD

- Highly Flammable (F)
- Irritant (Xi)
- Harmful (Xn)
- Substances Toxic To Reproduction - Category 3
- R11, R36, R48/20, R63, R66, R67

2.2 Label Elements

CLP

DANGER



- Hazard statements** • H225 - Highly flammable liquid and vapour
 H315 - Causes skin irritation
 H319 - Causes serious eye irritation
 H336 - May cause drowsiness or dizziness
 H361d - Suspected of damaging the unborn child.
 H373 - May cause damage to organs through prolonged or repeated exposure.
 EUH066 - Repeated exposure may cause skin dryness or cracking.

Precautionary statements

- Prevention** • P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P210 - Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.
 P233 - Keep container tightly closed.
 P240 - Ground and/or bond container and receiving equipment.
 P241 - Use explosion-proof electrical/ventilating/lighting/equipment.
 P242 - Use only non-sparking tools.
 P243 - Take precautionary measures against static discharge.
 P260 - Do not breathe mist/vapours/spray.
 P264 - Wash thoroughly after handling.
 P271 - Use only outdoors or in a well-ventilated area.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P281 - Use personal protective equipment as required.

- Response** • P370+P378 - In case of fire: Use appropriate media for extinction.
 P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
 P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P321 - Specific treatment, see supplemental first aid information.
 P332+P313 - If skin irritation occurs: Get medical advice/attention.
 P362 - Take off contaminated clothing and wash before reuse.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313 - If eye irritation persists: Get medical advice/attention.
 P308+P313 - IF exposed or concerned: Get medical advice/attention.

- Storage/Disposal** • P233 - Keep container tightly closed.
 P403+P235 - Store in a well-ventilated place. Keep cool.
 P501 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

DSD/DPD



- Risk phrases** • R11 - Highly flammable.
 R36 - Irritating to eyes.
 R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 R63 - Possible risk of harm to the unborn child.
 R66 - Repeated exposure may cause skin dryness or cracking.
 R67 - Vapours may cause drowsiness and dizziness.

- Safety phrases** • S9 - Keep container in a well ventilated place
 S16 - Keep away from sources of ignition - No Smoking.
 S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 S37 - Wear suitable gloves.

2.3 Other Hazards

- | | |
|----------------|-------------------------------------------------------------------------------------------|
| CLP | • According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous. |
| DSD/DPD | • According to European Directive 1999/45/EC this preparation is considered dangerous. |

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

2.1 Classification of the substance or mixture

- | | |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OSHA HCS 2012 | <ul style="list-style-type: none"> • Flammable Liquids 2 • Skin Irritation 2 • Eye Irritation 2A • Acute Toxicity Inhalation 4 • Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects • Reproductive Toxicity 2 |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

2.2 Label elements

OSHA HCS 2012

DANGER



- Hazard statements**
- Highly flammable liquid and vapour
 - Causes skin irritation
 - Causes serious eye irritation
 - Harmful if inhaled
 - May cause respiratory irritation
 - May cause drowsiness or dizziness
 - Suspected of damaging fertility or the unborn child.

Precautionary statements

- Prevention**
- Obtain special instructions before use.
 - Do not handle until all safety precautions have been read and understood.
 - Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.
 - Keep container tightly closed.
 - Ground and/or bond container and receiving equipment.
 - Use explosion-proof electrical/ventilating/lighting/equipment.
 - Use only non-sparking tools.
 - Take precautionary measures against static discharge.
 - Do not breathe the mist/vapours/spray.
 - Wash thoroughly after handling.
 - Use only outdoors or in a well-ventilated area.
 - Wear protective gloves/protective clothing/eye protection/face protection.
- Response**
- In case of fire: Use appropriate media for extinction.
 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 - Call a POISON CENTER or doctor/physician if you feel unwell.
 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 - Specific treatment, see supplemental first aid information.
 - If skin irritation occurs: Get medical advice/attention.
 - Take off contaminated clothing and wash before reuse.
 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - If eye irritation persists: Get medical advice/attention.
 - IF exposed or concerned: Get medical advice/attention.
- Storage/Disposal**
- Keep container tightly closed.
 - Store in a well-ventilated place. Keep cool.

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

2.3 Other hazards

OSHA HCS 2012

- Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Canada

According to: WHMIS

2.1 Classification of the substance or mixture

WHMIS

- Flammable Liquids - B2
- Other Toxic Effects - D2A
- Other Toxic Effects - D2B

2.2 Label elements

WHMIS



WHMIS

- Flammable Liquids - B2
- Other Toxic Effects - D2A
- Other Toxic Effects - D2B

2.3 Other hazards

WHMIS

- In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

See Section 12 for Ecological Information.

Section 3 - Composition/Information on Ingredients

3.1 Substances

- Material does not meet the criteria of a substance in accordance with Regulation (EC) No 1272/2008.

3.2 Mixtures

Composition					
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments
Acetic acid, tert-butyl ester	CAS:540-88-5 EC Number:208-760-7	25% TO 50%	Ingestion/Oral-Rat LD50 • 4100 mg/kg Inhalation-Rat LC50 • >2230 mg/m ³ 4 Hour (s) Skin-Rabbit LD50 • >2 g/kg	EU DSD/DPD: Annex I: F; R11; R66 EU CLP: EU CLP, Annex VI, Table 3.1: Flam. Liq. 2, H225 OSHA HCS 2012: Flam. Liq. 2; Acute Tox . 3 (Inhl.)	NDA
Acetic acid, methyl ester	CAS:79-20-9 EC Number:201-185-2	25% TO 50%	Ingestion/Oral-Rat LD50 • >5 g/kg Skin-Rabbit LD50 • >5 g/kg	EU DSD/DPD: Annex I: F; R11; Xi; R36; R66; R67 EU CLP: Annex VI: Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3: Narc., H336; EUH066 OSHA HCS 2012:	NDA

Toluene	CAS:108-88-3 EC Number:203-625-9	2.5% TO 10%	Ingestion/Oral-Rat LD50 • 636 mg/kg Inhalation-Rat LC50 • 49 g/m ³ 4 Hour(s) Skin-Rabbit LD50 • 14100 µL/kg	EU DSD/DPD: Annex I: F; R11; Repr. 3; R63; Xn; R48/20-65; Xi; R38; R67 EU CLP: Annex VI: Flam. Liq. 2, H225; Repr. 2, H361d; Asp. Tox. 1, H304; STOT RE 2, H373; Skin Irrit. 2, H315; STOT SE 3: Narc., H336 OSHA HCS 2012: Flam. Liq. 2; Repr. 2; Acute Tox. 4 (Oral); STOT SE 3: Narc.; Asp. Tox. 1; Eye Irrit. 2B	NDA
Phenolic Resin	NDA	2.5% TO 10%	NDA	EU DSD/DPD: Data Lacking EU CLP: Data Lacking OSHA HCS 2012: Data Lacking	NDA

See Section 16 for full text of H-statements and R-phrases. See Section 11 for Toxicological Information.

Section 4 - First Aid Measures

4.1 Description of first aid measures

- Inhalation**
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. If signs/symptoms continue, get medical attention.
- Skin**
- In case of contact with substance, immediately flush skin with running water for at least 20 minutes. Wash skin with soap and water. If skin irritation occurs: Get medical advice/attention.
- Eye**
- In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.
- Ingestion**
- Rinse mouth. Drink 1 - 2 glasses of water. Do not give anything by mouth to an unconscious person. Do NOT induce vomiting. Get medical attention.

4.2 Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to Physician**
- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Section 5 - Firefighting Measures

5.1 Extinguishing media

- Suitable Extinguishing Media**
- LARGE FIRES: Water spray, fog or alcohol-resistant foam.
SMALL FIRES: Dry chemical, CO₂, water spray or alcohol-resistant foam.
- Unsuitable Extinguishing Media**
- Do not use a direct stream of water.

5.2 Special hazards arising from the substance or mixture

- Unusual Fire and Explosion Hazards**
- HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Containers may explode when heated.
Vapor explosion hazard indoors, outdoors or in sewers.
Many liquids are lighter than water.
Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).
Runoff to sewer may create fire or explosion hazard.
Vapors may form explosive mixtures with air.
Vapors may travel to source of ignition and flash back.
Dried solids can burn and release toxic fumes and vapors.
- Hazardous Combustion Products**
- No data available

5.3 Advice for firefighters

- No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if you can do it without risk. Structural firefighters' protective clothing will only provide limited protection. Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection. Wear positive pressure self-contained breathing apparatus (SCBA).

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Precautions

- Ventilate enclosed areas. Wear appropriate protective clothing. Do not touch or walk through spilled material.

Emergency Procedures

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions. LARGE SPILL: Consider initial downwind evacuation for at least 300 meters (1000 feet) Keep out of low areas. Stay upwind. Keep unauthorized personnel away. Ventilate closed spaces before entering.

6.2 Environmental precautions

- Prevent entry into waterways, sewers, basements or confined areas.

6.3 Methods and material for containment and cleaning up

Containment/Clean-up Measures

- Stop leak if you can do it without risk.
A vapor suppressing foam may be used to reduce vapors.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use clean non-sparking tools to collect absorbed material.
All equipment used when handling the product must be grounded.

6.4 Reference to other sections

- Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Handling

- Keep away from fire. Keep away from heat and sparks. Do not eat, drink or smoke when using this product. After handling wash hands thoroughly. Prevent formation of aerosols. All equipment used when handling the product must be grounded. Bond and ground all transfer containers and equipment. Take precautionary measures against static charges. Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations near container.

7.2 Conditions for safe storage, including any incompatibilities

Storage

- Keep containers properly sealed in a cool, dry, well-ventilated area between 65-85F (18.3-29.4C). Do not store in open, unlabeled or mislabeled containers. Do not reuse empty container without commercial cleaning or reconditioning.

7.3 Specific end use(s)

- Refer to Section 1.2 - Relevant identified uses.

Section 8 - Exposure Controls/Personal Protection

8.1 Control parameters

Exposure Limits/Guidelines						
	Result	ACGIH	Canada Alberta	Canada British Columbia	Canada Manitoba	Canada New Brunswick
Toluene (108-88-3)	TWAs	20 ppm TWA	50 ppm TWA; 188 mg/m ³ TWA	20 ppm TWA	20 ppm TWA	50 ppm TWA; 188 mg/m ³ TWA
Acetic acid, methyl ester (79-20-9)	STELs	250 ppm STEL	250 ppm STEL; 757 mg/m ³ STEL	250 ppm STEL	250 ppm STEL	250 ppm STEL; 757 mg/m ³ STEL
	TWAs	200 ppm TWA	200 ppm TWA; 606 mg/m ³ TWA	200 ppm TWA	200 ppm TWA	200 ppm TWA; 606 mg/m ³ TWA
Acetic acid, tert-butyl ester (540-88-5)	TWAs	200 ppm TWA	200 ppm TWA; 950 mg/m ³ TWA	200 ppm TWA	200 ppm TWA	200 ppm TWA; 950 mg/m ³ TWA
Exposure Limits/Guidelines (Con't.)						
	Result	Canada Northwest Territories	Canada Nova Scotia	Canada Nunavut	Canada Ontario	Canada Quebec
Toluene (108-88-3)	STELs	150 ppm STEL; 560 mg/m ³ STEL	Not established	150 ppm STEL; 560 mg/m ³ STEL	Not established	Not established
	TWAs	100 ppm TWA; 375 mg/m ³ TWA	20 ppm TWA	100 ppm TWA; 375 mg/m ³ TWA	20 ppm TWA	50 ppm TWAEV; 188 mg/m ³ TWAEV
Acetic acid, methyl ester (79-20-9)	STELs	250 ppm STEL; 760 mg/m ³ STEL	250 ppm STEL	250 ppm STEL; 760 mg/m ³ STEL	250 ppm STEL	250 ppm STEV; 757 mg/m ³ STEV
	TWAs	200 ppm TWA; 605 mg/m ³ TWA	200 ppm TWA	200 ppm TWA; 605 mg/m ³ TWA	200 ppm TWA	200 ppm TWAEV; 606 mg/m ³ TWAEV
Acetic acid, tert-butyl ester (540-88-5)	STELs	250 ppm STEL; 1187 mg/m ³ STEL	Not established	250 ppm STEL; 1187 mg/m ³ STEL	Not established	Not established
	TWAs	200 ppm TWA; 950 mg/m ³ TWA	200 ppm TWA	200 ppm TWA; 950 mg/m ³ TWA	200 ppm TWA	200 ppm TWAEV; 950 mg/m ³ TWAEV
Exposure Limits/Guidelines (Con't.)						
	Result	Canada Saskatchewan	Canada Yukon	Europe	NIOSH	OSHA
Toluene (108-88-3)	STELs	Not established	150 ppm STEL; 560 mg/m ³ STEL	100 ppm STEL; 384 mg/m ³ STEL	150 ppm STEL; 560 mg/m ³ STEL	Not established
	TWAs	50 ppm TWA	100 ppm TWA; 375 mg/m ³ TWA	50 ppm TWA; 192 mg/m ³ TWA	100 ppm TWA; 375 mg/m ³ TWA	200 ppm TWA
	Ceilings	Not established	Not established	Not established	Not established	300 ppm Ceiling
Acetic acid, methyl ester (79-20-9)	TWAs	200 ppm TWA	200 ppm TWA; 610 mg/m ³ TWA	Not established	200 ppm TWA; 610 mg/m ³ TWA	200 ppm TWA; 610 mg/m ³ TWA
	STELs	Not established	250 ppm STEL; 760 mg/m ³ STEL	Not established	250 ppm STEL; 760 mg/m ³ STEL	Not established
Acetic acid, tert-butyl ester (540-88-5)	TWAs	200 ppm TWA	200 ppm TWA; 950 mg/m ³ TWA	Not established	200 ppm TWA; 950 mg/m ³ TWA	200 ppm TWA; 950 mg/m ³ TWA
	STELs	Not established	250 ppm STEL; 1180 mg/m ³ STEL	Not established	Not established	Not established

8.2 Exposure controls

Engineering Measures/Controls

- Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof electrical/ventilating/lighting/equipment.

Personal Protective Equipment

Respiratory

- In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face

- Wear splash goggles.

Skin/Body

- Wear clothing and footwear that cannot be penetrated by chemicals or oil.

General Industrial Hygiene Considerations

- Avoid contact with skin, eyes or clothing. Keep away from food, drink and animal feeding stuffs. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Handle in accordance with good industrial hygiene and safety practice.

Environmental Exposure Controls

- Follow best practice for site management and disposal of waste. Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

NIOSH = National Institute of Occupational Safety and Health

OSHA = Occupational Safety and Health Administration

STEL = Short Term Exposure Limits are based on 15-minute exposures

STEV = Short Term Exposure Value

TWAEV = Time-Weighted Average Exposure Value

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

Section 9 - Physical and Chemical Properties**9.1 Information on Basic Physical and Chemical Properties**

Material Description			
Physical Form	Liquid	Appearance/Description	Light liquid with a characteristic odor.
Color	Light	Odor	Characteristic
Odor Threshold	Data lacking		
General Properties			
Boiling Point	57 °C(134.6 °F)	Melting Point/Freezing Point	Data lacking
Decomposition Temperature	Data lacking	pH	Data lacking
Specific Gravity/Relative Density	Data lacking	Water Solubility	Immiscible
Viscosity	Data lacking	Explosive Properties	Not explosive.
Oxidizing Properties:	Not an oxidizer.		
Volatility			
Vapor Pressure	Data lacking	Vapor Density	Data lacking
Evaporation Rate	Data lacking		
Flammability			
Flash Point	-10 °C(14 °F)	UEL	16 %
LEL	3.1 %	Autoignition	455 °C(851 °F)
Flammability (solid, gas)	Flammable Liquid.		
Environmental			
Octanol/Water Partition coefficient	Data lacking		

9.2 Other Information

- No additional physical and chemical parameters noted.

Section 10: Stability and Reactivity

10.1 Reactivity

- No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

- Stable under normal temperatures and pressures.

10.3 Possibility of hazardous reactions

- Hazardous polymerization will not occur.

10.4 Conditions to avoid

- Avoid flames, sparks, or other sources of ignition.

10.5 Incompatible materials

- Oxidizing agents.

10.6 Hazardous decomposition products

- Carbon monoxide, carbon dioxide, and hydrocarbons.

Section 11 - Toxicological Information

11.1 Information on toxicological effects

Components		
Toluene (2.5% TO 10%)	108-88-3	Acute Toxicity: Ingestion/Oral-Rat LD50 • 636 mg/kg; Inhalation-Rat LC50 • 49 g/m ³ 4 Hour(s); Skin-Rabbit LD50 • 14100 µL/kg; Irritation: Eye-Rabbit • 100 mg 30 Second(s)-Rinse • Mild irritation; Skin-Rabbit • 435 mg • Mild irritation; Reproductive: Inhalation-Rat TLo • 1500 ppm (7-20D preg); <i>Reproductive Effects:Specific Developmental Abnormalities:Central nervous system; Reproductive Effects:Effects on Newborn:Growth statistics (e.g., reduced weight gain); Reproductive Effects:Effects on Newborn:Biochemical and metabolic</i>
Acetic acid, methyl ester (25% TO 50%)	79-20-9	Acute Toxicity: Ingestion/Oral-Rat LD50 • >5 g/kg; Skin-Rabbit LD50 • >5 g/kg; Irritation: Eye-Rabbit • 100 mg 24 Hour(s) • Moderate irritation; Skin-Rabbit • 20 mg 24 Hour(s) • Moderate irritation
Acetic acid, tert-butyl ester (25% TO 50%)	540-88-5	Acute Toxicity: Ingestion/Oral-Rat LD50 • 4500 mg/kg; Inhalation-Rat LC50 • >2230 mg/m ³ 4 Hour(s); Skin-Rabbit LD50 • >2 g/kg; <i>Gastrointestinal:Hypermotility, diarrhea; Kidney, Ureter, and Bladder:Other changes;</i> Irritation: Skin-Rabbit • 500 µL 24 Hour(s) • Mild irritation

GHS Properties	Classification
Acute toxicity	EU/CLP • Classification criteria not met OSHA HCS 2012 • Acute Toxicity - Inhalation 4
Skin corrosion/Irritation	EU/CLP • Skin Irritation 2 OSHA HCS 2012 • Skin Irritation 2
Serious eye damage/Irritation	EU/CLP • Eye Irritation 2 OSHA HCS 2012 • Eye Irritation 2A
Skin sensitization	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Respiratory sensitization	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Aspiration Hazard	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Carcinogenicity	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met

Germ Cell Mutagenicity	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Toxicity for Reproduction	EU/CLP • Toxic to Reproduction 2 OSHA HCS 2012 • Toxic to Reproduction 2
STOT-SE	EU/CLP • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects OSHA HCS 2012 • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects; Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation
STOT-RE	EU/CLP • Specific Target Organ Toxicity Repeated Exposure 2 OSHA HCS 2012 • Classification criteria not met

Route(s) of entry/exposure • Inhalation, Skin, Eye, Ingestion

Potential Health Effects

Inhalation

- Acute (Immediate)** • Harmful if inhaled. May cause respiratory irritation. May affect the central nervous system. Symptoms may include dizziness, drowsiness, lethargy, coma and death.
- Chronic (Delayed)** • No data available

Skin

- Acute (Immediate)** • Causes skin irritation.
- Chronic (Delayed)** • Repeated exposure may cause skin dryness or cracking.

Eye

- Acute (Immediate)** • Causes serious eye irritation.
- Chronic (Delayed)** • No data available.

Ingestion

- Acute (Immediate)** • Although swallowing this product is an unlikely means of exposure, irritation of the mouth, pharynx, esophagus and stomach can develop following ingestion.
- Chronic (Delayed)** • No data available.

Other

- Chronic (Delayed)** • May cause damage to organs through prolonged or repeated exposure.

Carcinogenic Effects

- The ingredients of this product are not classified as carcinogenic by ACGIH or IARC, not regulated as carcinogens by OSHA, and not listed as carcinogens by NTP.

Reproductive Effects

- Repeated or prolonged exposure to toluene may cause reproductive effects.

Key to abbreviations

LC = Lethal Concentration MOD = Moderate
LD = Lethal Dose TC = Toxic Concentration
MLD = Mild

Section 12 - Ecological Information

12.1 Toxicity

	CAS	
All Purpose Bonding Adhesive LVOC	NDA	Aquatic Toxicity-Crustacea: 48 Hour(s) EC50 Water Flea <i>Daphnia magna</i> 6.8 mg/L Comments: Toluene 48 Hour(s) NOEC Water Flea <i>Daphnia magna</i> 28 mg/L Comments: Toluene

12.2 Persistence and degradability

- Material data lacking.

12.3 Bioaccumulative potential

- Material data lacking.

12.4 Mobility in Soil

- Material data lacking.

12.5 Results of PBT and vPvB assessment

- No PBT and vPvB assessment has been conducted.

12.6 Other adverse effects

- No studies have been found.

12.7 Other Information

- Water hazard class 2 (Self-assessment): hazardous to water. Do not allow product to reach sewage system. Disposal must be made according to official regulations.

Section 13 - Disposal Considerations

13.1 Waste treatment methods

Product waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	UN1133	Adhesives	3	II	NDA
TDG	UN1133	ADHESIVES	3	II	NDA
IMO/IMDG	UN1133	ADHESIVES	3	II	NDA
ADN	UN1133	ADHESIVES	3	II	NDA
ADR/RID	UN1133	ADHESIVES	3	II	NDA
IATA/ICAO	UN1133	Adhesives	3	II	NDA

14.6 Special precautions for user

- None known.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

- Not relevant.

Section 15 - Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications

- Acute, Chronic, Fire

State Right To Know				
Component	CAS	MA	NJ	PA
Acetic acid, methyl ester	79-20-9	Yes	Yes	Yes

Acetic acid, tert-butyl ester	540-88-5	Yes	Yes	Yes
Toluene	108-88-3	Yes	Yes	Yes

Inventory						
Component	CAS	Canada DSL	Canada NDSL	EU EINECS	EU ELNICS	TSCA
Acetic acid, methyl ester	79-20-9	Yes	No	Yes	No	Yes
Acetic acid, tert-butyl ester	540-88-5	Yes	No	Yes	No	Yes
Toluene	108-88-3	Yes	No	Yes	No	Yes

Canada

Labor

Canada - WHMIS - Classifications of Substances

• Acetic acid, methyl ester	79-20-9	B2, D2B
• Acetic acid, tert-butyl ester	540-88-5	B2
• Toluene	108-88-3	B2, D2A, D2B

Canada - WHMIS - Ingredient Disclosure List

• Acetic acid, methyl ester	79-20-9	1 %
• Acetic acid, tert-butyl ester	540-88-5	1 %
• Toluene	108-88-3	1 %

Environment

Canada - CEPA - Priority Substances List

• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed
• Toluene	108-88-3	Priority Substance List 1 (substance not considered toxic)

Europe

Other

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification

• Acetic acid, methyl ester	79-20-9	F; R11 Xi; R36 R66 R67
• Acetic acid, tert-butyl ester	540-88-5	F; R11 R66
• Toluene	108-88-3	F; R11 Xi; R38 Xn; R48/20-65 Repr.Cat.3; R63 R67

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits

• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed
• Toluene	108-88-3	Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling

• Acetic acid, methyl ester	79-20-9	F Xi R:11-36-66-67 S:(2)-16-26-29-33
• Acetic acid, tert-butyl ester	540-88-5	F R:11-66 S:(2)-16-23-25-29-33
• Toluene	108-88-3	F Xn R:11-38-48/20-63-65-67 S:(2)-36/37-46-62

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Preparations

• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	C
• Toluene	108-88-3	Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases

• Acetic acid, methyl ester	79-20-9	S:(2)-16-26-29-33
• Acetic acid, tert-butyl ester	540-88-5	S:(2)-16-23-25-29-33
• Toluene	108-88-3	S:(2)-36/37-46-62

United States**Labor****U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals**

• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed
• Toluene	108-88-3	Not Listed

U.S. - OSHA - Specifically Regulated Chemicals

• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed
• Toluene	108-88-3	Not Listed

Environment**U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants**

• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed
• Toluene	108-88-3	

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	5000 lb final RQ (listed under Butyl acetate); 2270 kg final RQ (listed under Butyl acetate)
• Toluene	108-88-3	1000 lb final RQ; 454 kg final RQ

U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities

• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed
• Toluene	108-88-3	Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed
• Toluene	108-88-3	Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed
• Toluene	108-88-3	Not Listed

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed
• Toluene	108-88-3	1.0 % de minimis concentration

U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing

• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed
• Toluene	108-88-3	Not Listed

U.S. - RCRA (Resource Conservation & Recovery Act) - Basis for Listing - Appendix VII

• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed
• Toluene	108-88-3	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151

U.S. - RCRA (Resource Conservation & Recovery Act) - Constituents for Detection Monitoring

• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed
• Toluene	108-88-3	

U.S. - RCRA (Resource Conservation & Recovery Act) - Hazardous Constituents - Appendix VIII to 40 CFR 261

• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed
• Toluene	108-88-3	waste number U220

U.S. - RCRA (Resource Conservation & Recovery Act) - List for Hazardous Constituents

• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed
• Toluene	108-88-3	

U.S. - RCRA (Resource Conservation & Recovery Act) - Phase 4 LDR Rule - Universal Treatment Standards

• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed
• Toluene	108-88-3	0.080 mg/L (wastewater); 10 mg/kg (nonwastewater)

U.S. - RCRA (Resource Conservation & Recovery Act) - TSD Facilities Ground Water Monitoring

• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed
• Toluene	108-88-3	

U.S. - RCRA (Resource Conservation & Recovery Act) - U Series Wastes - Acutely Toxic Wastes & Other Hazardous Characteristics

• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed
• Toluene	108-88-3	waste number U220

United States - California**Environment****U.S. - California - Proposition 65 - Carcinogens List**

• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed
• Toluene	108-88-3	Not Listed

U.S. - California - Proposition 65 - Developmental Toxicity

• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed

• Toluene	108-88-3	developmental toxicity, initial date 1/1/91
U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)		
• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed
• Toluene	108-88-3	7000 µg/day MADL (level represents absorbed dose)
U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)		
• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed
• Toluene	108-88-3	Not Listed
U.S. - California - Proposition 65 - Reproductive Toxicity - Female		
• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed
• Toluene	108-88-3	female reproductive toxicity, initial date 8/7/09
U.S. - California - Proposition 65 - Reproductive Toxicity - Male		
• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed
• Toluene	108-88-3	Not Listed

United States - Pennsylvania

Labor

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	
• Toluene	108-88-3	

U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances

• Acetic acid, methyl ester	79-20-9	Not Listed
• Acetic acid, tert-butyl ester	540-88-5	Not Listed
• Toluene	108-88-3	Not Listed

15.2 Chemical Safety Assessment

- No Chemical Safety Assessment has been carried out.

15.3 Other Information

- WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Section 16 - Other Information

Relevant Phrases (code & full text)

- H304 - May be fatal if swallowed and enters airways
- R38 - Irritating to skin.
- R65 - Harmful: may cause lung damage if swallowed.

Revision Date

- 28/February/2018

Preparation Date

- 03/February/2012

Other Information

- Changes to this revision: Updated mailing address.

Disclaimer/Statement of Liability

- The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information, is accurate, complete or representative. Firestone Building Products Company, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons, if reasonable safety procedures are not followed. Additionally, Firestone Building Products Company assumes no responsibility for injury to buyer, the buyer's employees, or any third persons caused by abnormal use of this material, even if reasonable safety procedures are followed.

Key to abbreviations

NDA = No data available