

Safety Data Sheet

Firestone Building Products Company

Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier

Product Name • UltraPly™ TPO Cut Edge Sealant White

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified use(s) • Construction

1.3 Details of the supplier of the safety data sheet

Manufacturer • Firestone Building Products Company
200 4th Avenue S
Nashville, TN 37201-2208
United States

firestonemsds@bfdp.com

Telephone (General) • 800-428-4442

1.4 Emergency telephone number

Manufacturer • (800) 424-9300 - CHEMTREC

Manufacturer • (703) 527-3887 - CHEMTREC - International

Section 2: Hazards Identification

EU/EEC

According to: Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010]

According to: EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

2.1 Classification of the substance or mixture

- CLP**
- Flammable Liquids 3 - H226
 - Aspiration 1 - H304
 - Acute Toxicity Dermal 4 - H312
 - Skin Irritation 2 - H315
 - Acute Toxicity Inhalation 4 - H332
 - Germ Cell Mutagenicity 1B - H340
 - Carcinogenicity 1B - H350
- DSD/DPD**
- Flammable
 - Harmful (Xn)
 - Irritant (Xi)
 - Mutagenic Substances - Category 2
 - Carcinogenic Substances - Category 2
 - R10, R20/21, R38, R45, R65

2.2 Label Elements

CLP

DANGER



- Hazard statements** • H226 - Flammable liquid and vapour
 H304 - May be fatal if swallowed and enters airways
 H312 - Harmful in contact with skin
 H315 - Causes skin irritation
 H332 - Harmful if inhaled
 H340 - May cause genetic defects.
 H350 - May cause cancer.

Precautionary statements

- Prevention** • P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P210 - Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.
 P233 - Keep container tightly closed.
 P240 - Ground and/or bond container and receiving equipment.
 P241 - Use explosion-proof electrical/ventilating/lighting/equipment.
 P242 - Use only non-sparking tools.
 P243 - Take precautionary measures against static discharge.
 P261 - Avoid breathing mist/vapours/spray.
 P264 - Wash thoroughly after handling.
 P271 - Use only outdoors or in a well-ventilated area.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P281 - Use personal protective equipment as required.

- Response** • P370+P378 - In case of fire: Use appropriate media for extinction.
 P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
 P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P321 - Specific treatment, see supplemental first aid information.
 P362 - Take off contaminated clothing and wash before reuse.
 P363 - Wash contaminated clothing before reuse.
 P332+P313 - If skin irritation occurs: Get medical advice/attention.
 P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 P331 - Do NOT induce vomiting.
 P308+P313 - IF exposed or concerned: Get medical advice/attention.

- Storage/Disposal** • P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
 P235 - Keep cool.
 P501 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

- Supplemental information** • 5 percent of this product consists of an ingredient of unknown oral toxicity.
 20 percent of this product consists of an ingredient of unknown inhalation toxicity.

DSD/DPD



- Risk phrases** • R10 - Flammable.
 R20/21 - Harmful by inhalation and in contact with skin.
 R38 - Irritating to skin.
 R45 - May cause cancer.
 R65 - Harmful: may cause lung damage if swallowed.

- Safety phrases** • S23 - Do not breathe gas/fumes/vapour/spray.
 S36 - Wear suitable protective clothing.
 S53 - Avoid exposure - obtain special instructions before use.

2.3 Other Hazards

- CLP** • According to Regulation (EC) No. 1272/2008 (CLP) this material is considered

- hazardous.
- DSD/DPD**
- According to European Directive 1999/45/EC this material is considered dangerous.

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

2.1 Classification of the substance or mixture

OSHA HCS 2012

- Flammable Liquids 3
- Aspiration 1
- Acute Toxicity Dermal 4
- Skin Irritation 2
- Eye Irritation 2
- Acute Toxicity Inhalation 4
- Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation
- Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects
- Carcinogenicity 2
- Reproductive Toxicity 2
- Specific Target Organ Toxicity Repeated Exposure 1

2.2 Label elements

OSHA HCS 2012

DANGER



- Hazard statements**
- Flammable liquid and vapour
 - May be fatal if swallowed and enters airways
 - Harmful in contact with skin
 - Causes skin irritation
 - Causes serious eye irritation
 - Harmful if inhaled
 - May cause respiratory irritation
 - May cause drowsiness or dizziness
 - Suspected of causing cancer.
 - Suspected of damaging fertility or the unborn child.
 - Causes damage to organs - liver/kidney through prolonged or repeated exposure

Precautionary statements

- Prevention**
- Obtain special instructions before use.
 - Do not handle until all safety precautions have been read and understood.
 - Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.
 - Keep container tightly closed.
 - Ground and/or bond container and receiving equipment.
 - Use explosion-proof electrical/ventilating/lighting/equipment.
 - Use only non-sparking tools.
 - Take precautionary measures against static discharge.
 - Do not breathe mist/vapours/spray.
 - Wash thoroughly after handling.
 - Do not eat, drink or smoke when using this product.
 - Use only outdoors or in a well-ventilated area.
 - Wear protective gloves/protective clothing/eye protection/face protection.
- Response**
- In case of fire: Use appropriate media for extinction.
 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 - Call a POISON CENTER or doctor/physician if you feel unwell.
 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 - Specific treatment, see supplemental first aid information.
 - If skin irritation occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Do NOT induce vomiting.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Storage/Disposal • Store in a well-ventilated place. Keep container tightly closed.

Keep cool.

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Supplemental information • 5 percent of this product consists of an ingredient of unknown toxicity.

2.3 Other hazards

OSHA HCS 2012

- Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Canada

According to: WHMIS

2.1 Classification of the substance or mixture

WHMIS

- Flammable Liquids - B2
- Other Toxic Effects - D2A
- Other Toxic Effects - D2B

2.2 Label elements

WHMIS



WHMIS

- Flammable Liquids - B2
- Other Toxic Effects - D2A
- Other Toxic Effects - D2B

2.3 Other hazards

WHMIS

- In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

Section 3 - Composition/Information on Ingredients

3.1 Substances

- Material does not meet the criteria of a substance in accordance with Regulation (EC) No 1272/2008.

3.2 Mixtures

Composition					
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments

Xylene	CAS: 1330-20-7 EC Number: 215-535-7	50% TO 100%	Ingestion/Oral-Rat LD50 • 4300 mg/kg Inhalation-Rat LC50 • 5000 ppm 4 Hour(s) Skin-Rabbit LD50 • >1700 mg/kg	EU DSD/DPD: EU CLP, Annex VI, Table 3.2: R10; Xn, R20/21; Xi, R38 EU CLP: Annex VI: Flam. Liq. 3, H225; Acute Tox. 4, H332; Acute Tox. 4, H312; Skin Irrit. 2, H315 OSHA HCS 2012: Flam Liq. 3; Acute Tox. 4 (Skin); Eye Irrit. 2; Skin Irrit. 2; Repr. 2; STOT SE 3: Resp. Irrit. & Narc.	NDA
Stoddard solvent	CAS: 8052-41-3 EC Number: 232-489-3	5% TO 20%	Inhalation-Rat LC50 • >1400 ppm 8 Hour(s)	EU DSD/DPD: EU CLP, Annex VI, Table 3.2: Carc.Cat.2, R45; Muta.Cat.2, R46; Xn, R48/20, R65 EU CLP: Annex VI: Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304 OSHA HCS 2012: Flam. Liq. 3; Eye Irrit. 2A; Skin Irrit. 2; STOT RE 1 (Liver, Kidney); STOT SE 3: Narc.; Asp. Tox. 1	NDA
Ethylbenzene	CAS: 100-41-4 EC Number: 202-849-4	5% TO 20%	Ingestion/Oral-Rat LD50 • 3500 mg/kg Skin-Rabbit LD50 • 17800 µL/kg Inhalation-Rat LC50 • 55000 mg/m ³ 2 Hour(s)	EU DSD/DPD: EU CLP, Annex VI, Table 3.2: F, R11; Xn, R20, R48/20, R65 EU CLP: Annex VI: Flam. Liq. 2, H225; Acute Tox. 4, H332 OSHA HCS 2012: Flam. Liq. 2; Eye Irrit. 2A, Repr. 2.; Carc. 2; STOT SE 3: Resp. Irrit.; STOT SE 3: Narc.	NDA

Section 4 - First Aid Measures

4.1 Description of first aid measures

Inhalation

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. If signs/symptoms continue, get medical attention.

Skin

- In case of contact with substance, immediately flush skin with running water for at least 20 minutes. Wash skin with soap and water. If skin irritation occurs: Get medical advice/attention.

Eye

- In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.

Ingestion

- Get medical attention.

4.2 Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician

- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Section 5 - Firefighting Measures

5.1 Extinguishing media

Suitable Extinguishing Media

- LARGE FIRES: Water spray, fog or alcohol-resistant foam.
SMALL FIRES: Dry chemical, CO₂, water spray or alcohol-resistant foam.

Unsuitable Extinguishing Media

- Do not use a direct stream of water.

5.2 Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

- HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Containers may explode when heated.
Vapor explosion hazard indoors, outdoors or in sewers.

Many liquids are lighter than water.
 Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).
 Runoff to sewer may create fire or explosion hazard.
 Vapors may form explosive mixtures with air.
 Vapors may travel to source of ignition and flash back.
 Dried solids can burn and release toxic fumes and vapors.

Hazardous Combustion Products

- No data available

5.3 Advice for firefighters

- No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if you can do it without risk. Structural firefighters' protective clothing will only provide limited protection. Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection. Wear positive pressure self-contained breathing apparatus (SCBA).

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Precautions

- Do not walk through spilled material. Wear appropriate personal protective equipment, avoid direct contact. Do not breathe mist/vapours/spray. Avoid contact with skin, eyes, and clothing. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Emergency Procedures

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions. LARGE SPILL: Consider initial downwind evacuation for at least 300 meters (1000 feet) Keep out of low areas. Stay upwind. Keep unauthorized personnel away. Ventilate closed spaces before entering.

6.2 Environmental precautions

- Prevent entry into waterways, sewers, basements or confined areas.

6.3 Methods and material for containment and cleaning up

Containment/Clean-up Measures

- Stop leak if you can do it without risk.
 A vapor suppressing foam may be used to reduce vapors.
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Use clean non-sparking tools to collect absorbed material.
 All equipment used when handling the product must be grounded.

6.4 Reference to other sections

- Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Handling

- Keep away from fire, sparks and heated surfaces. Use only in well ventilated areas. Wear appropriate personal protective equipment, avoid direct contact. Avoid contact with skin, eyes, and clothing. Do not breathe mist/vapours/spray. All equipment used when handling the product must be grounded. Prevent formation of aerosols. Bond and ground all transfer containers and equipment. Take precautionary measures against static charges. Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations near container. Do not eat, drink or smoke when using this product. After handling wash hands thoroughly.

7.2 Conditions for safe storage, including any incompatibilities

Storage

- Store in a cool/low-temperature, well-ventilated place away from heat and ignition sources. Keep container tightly closed. Store away from oxidizing agents.

7.3 Specific end use(s)

- Refer to Section 1.2 - Relevant identified uses.

Section 8 - Exposure Controls/Personal Protection

8.1 Control parameters

Exposure Limits/Guidelines						
	Result	ACGIH	Canada Alberta	Canada British Columbia	Canada Manitoba	Canada New Brunswick
Ethylbenzene (100-41-4)	STELs	Not established	125 ppm STEL; 543 mg/m ³ STEL	Not established	Not established	125 ppm STEL; 543 mg/m ³ STEL
	TWAs	20 ppm TWA	100 ppm TWA; 434 mg/m ³ TWA	20 ppm TWA	20 ppm TWA	100 ppm TWA; 434 mg/m ³ TWA
Stoddard solvent (8052-41-3)	TWAs	100 ppm TWA	100 ppm TWA; 572 mg/m ³ TWA	290 mg/m ³ TWA	100 ppm TWA	100 ppm TWA; 525 mg/m ³ TWA
	STELs	Not established	Not established	580 mg/m ³ STEL	Not established	Not established
Xylene (1330-20-7)	STELs	150 ppm STEL	150 ppm STEL; 651 mg/m ³ STEL	150 ppm STEL	150 ppm STEL	150 ppm STEL; 651 mg/m ³ STEL
	TWAs	100 ppm TWA	100 ppm TWA; 434 mg/m ³ TWA	100 ppm TWA	100 ppm TWA	100 ppm TWA; 434 mg/m ³ TWA
Exposure Limits/Guidelines (Con't.)						
	Result	Canada Northwest Territories	Canada Nova Scotia	Canada Nunavut	Canada Ontario	Canada Quebec
Ethylbenzene (100-41-4)	STELs	125 ppm STEL; 542 mg/m ³ STEL	Not established	125 ppm STEL; 542 mg/m ³ STEL	Not established	125 ppm STEV; 543 mg/m ³ STEV
	TWAs	100 ppm TWA; 434 mg/m ³ TWA	20 ppm TWA	100 ppm TWA; 434 mg/m ³ TWA	20 ppm TWA	100 ppm TWA EV; 434 mg/m ³ TWA EV
Stoddard solvent (8052-41-3)	STELs	125 ppm STEL; 720 mg/m ³ STEL	Not established	125 ppm STEL; 720 mg/m ³ STEL	Not established	Not established
	TWAs	100 ppm TWA; 575 mg/m ³ TWA	100 ppm TWA	100 ppm TWA; 575 mg/m ³ TWA	525 mg/m ³ TWA (140°C Flash aliphatic solvent)	100 ppm TWA EV; 525 mg/m ³ TWA EV
Xylene (1330-20-7)	STELs	150 ppm STEL; 652 mg/m ³ STEL	150 ppm STEL	150 ppm STEL; 652 mg/m ³ STEL	150 ppm STEL	150 ppm STEV; 651 mg/m ³ STEV
	TWAs	100 ppm TWA; 434 mg/m ³ TWA	100 ppm TWA	100 ppm TWA; 434 mg/m ³ TWA	100 ppm TWA	100 ppm TWA EV; 434 mg/m ³ TWA EV
Exposure Limits/Guidelines (Con't.)						
	Result	Canada Saskatchewan	Canada Yukon	NIOSH	OSHA	
Ethylbenzene (100-41-4)	TWAs	100 ppm TWA	100 ppm TWA; 435 mg/m ³ TWA	100 ppm TWA; 435 mg/m ³ TWA	100 ppm TWA; 435 mg/m ³ TWA	
	STELs	Not established	125 ppm STEL; 545 mg/m ³ STEL	125 ppm STEL; 545 mg/m ³ STEL	Not established	
Stoddard solvent (8052-41-3)	TWAs	100 ppm TWA	100 ppm TWA; 575 mg/m ³ TWA	350 mg/m ³ TWA	500 ppm TWA; 2900 mg/m ³ TWA	
	STELs	Not established	150 ppm STEL; 720 mg/m ³ STEL	Not established	Not established	

	Ceilings	Not established	Not established	1800 mg/m3 Ceiling (15 min)	Not established
Xylene (1330-20-7)	TWAs	100 ppm TWA	100 ppm TWA; 435 mg/m3 TWA	Not established	100 ppm TWA; 435 mg/m3 TWA
	STELs	Not established	150 ppm STEL; 650 mg/m3 STEL	Not established	Not established

8.2 Exposure controls

Engineering Measures/Controls

- Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof electrical/ventilating/lighting/equipment.

Personal Protective Equipment

Respiratory

- In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face

- Wear splash goggles.

Skin/Body

- Wear appropriate chemical resistant clothing. Wear appropriate chemical resistant gloves.

Environmental Exposure Controls

- Follow best practice for site management and disposal of waste. Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

NIOSH = National Institute of Occupational Safety and Health

OSHA = Occupational Safety and Health Administration

STEL = Short Term Exposure Limits are based on 15-minute exposures

STEV = Short Term Exposure Value

TWAEV = Time-Weighted Average Exposure Value

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

Section 9 - Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Appearance/Description	White, viscous liquid with a characteristic odor.
Color	White	Odor	Characteristic
Odor Threshold	Data lacking		
General Properties			
Boiling Point	137 °C(278.6 °F)	Melting Point/Freezing Point	Data lacking
Decomposition Temperature	Data lacking	pH	Data lacking
Specific Gravity/Relative Density	= 0.939 Water=1	Bulk Density	7.81 lbs/gal
Water Solubility	Immiscible	Viscosity	Data lacking
Explosive Properties	Not explosive.	Oxidizing Properties:	Not an oxidizer.
Volatility			
Vapor Pressure	6.7 hPa @ 20 °C(68 °F)	Vapor Density	Data lacking
Evaporation Rate	Data lacking	VOC (Wt.)	5.97 lbs/gal
Flammability			
Flash Point	30 °C(86 °F)	UEL	7 %

LEL	1.1 %	Autoignition	Data lacking
Flammability (solid, gas)	Flammable Liquid.		
Environmental			
Octanol/Water Partition coefficient	Data lacking		

9.2 Other Information

- No additional physical and chemical parameters noted.

Section 10: Stability and Reactivity

10.1 Reactivity

- No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

- Stable under normal temperatures and pressures.

10.3 Possibility of hazardous reactions

- Hazardous polymerization will not occur.

10.4 Conditions to avoid

- Avoid flames, sparks, or other sources of ignition.

10.5 Incompatible materials

- Strong oxidizers, acids, and bases.

10.6 Hazardous decomposition products

- Carbon monoxide, carbon dioxide, aldehydes and hydrocarbons.

Section 11 - Toxicological Information

11.1 Information on toxicological effects

Components		
Xylene (50% TO 100%)	1330-20-7	Acute Toxicity: Ingestion/Oral-Mammal LD50 • 4300 mg/kg; Inhalation-Rat LC50 • 5000 ppm 4 Hour(s); Skin-Rabbit LD50 • >1700 mg/kg; Reproductive: Inhalation-Rat TCLo • 50 mg/m ³ 6 Hour(s)(1-21D preg); <i>Reproductive Effects:Effects on Fertility:Post-implantation mortality; Reproductive Effects:Effects on Embryo or Fetus:Fetotoxicity (except death, e.g., stunted fetus); Reproductive Effects:Specific Developmental Abnormalities:Craniofacial (including nose and tongue)</i>
Stoddard solvent (5% TO 20%)	8052-41-3	Irritation: Eye-Rabbit • 500 mg 24 Hour(s) • Moderate irritation
Ethylbenzene (5% TO 20%)	100-41-4	Acute Toxicity: Ingestion/Oral-Rat LD50 • 3500 mg/kg; Inhalation-Rat LC50 • 55000 mg/m ³ 2 Hour(s); Skin-Rabbit LD50 • 17800 µL/kg; Irritation: Eye-Rabbit • 500 mg • Severe irritation; Skin-Rabbit • 15 mg 24 Hour(s)-Open • Mild irritation; Multi-dose Toxicity: Inhalation-Rabbit TCLo • 100 mg/m ³ 4 Hour(s) 30 Week(s)-Intermittent; <i>Blood:Changes in serum composition (e.g., TP, bilirubin cholesterol); Blood:Other changes; Blood:Changes in leucocyte (WBC) count</i>

GHS Properties	Classification
Acute toxicity	EU/CLP • Acute Toxicity - Dermal 4; Acute Toxicity - Inhalation 4 OSHA HCS 2012 • Acute Toxicity - Dermal 4; Acute Toxicity - Inhalation 4

Skin corrosion/Irritation	EU/CLP • Skin Irritation 2 OSHA HCS 2012 • Skin Irritation 2
Serious eye damage/Irritation	EU/CLP • Classification criteria not met OSHA HCS 2012 • Eye Irritation 2
Skin sensitization	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Respiratory sensitization	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Aspiration Hazard	EU/CLP • Aspiration 1 OSHA HCS 2012 • Aspiration 1
Carcinogenicity	EU/CLP • Carcinogenicity 1B OSHA HCS 2012 • Carcinogenicity 2
Germ Cell Mutagenicity	EU/CLP • Germ Cell Mutagenicity 1B OSHA HCS 2012 • Classification criteria not met
Toxicity for Reproduction	EU/CLP • Classification criteria not met OSHA HCS 2012 • Toxic to Reproduction 2
STOT-SE	EU/CLP • Classification criteria not met OSHA HCS 2012 • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects; Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation
STOT-RE	EU/CLP • Classification criteria not met OSHA HCS 2012 • Specific Target Organ Toxicity Repeated Exposure 1

Route(s) of entry/exposure • Inhalation, Skin, Eye, Ingestion

Potential Health Effects

Inhalation

Acute (Immediate)

- Harmful if inhaled. May cause respiratory irritation. May affect the central nervous system. Symptoms may include dizziness, drowsiness, lethargy, coma and death.

Chronic (Delayed)

- No data available

Skin

Acute (Immediate)

- Harmful in contact with skin. Causes skin irritation.

Chronic (Delayed)

- No data available

Eye

Acute (Immediate)

- Causes serious eye irritation.

Chronic (Delayed)

- No data available.

Ingestion

Acute (Immediate)

- Material may be aspirated into the lungs during ingestion and/or subsequent vomiting. Aspiration of this material will cause severe lung injury, chemical pneumonitis, pulmonary edema or death.

Chronic (Delayed)

- No data available.

Other

Chronic (Delayed)

- Prolonged or repeated exposure causes damage to liver and kidneys.

Mutagenic Effects

- Repeated and prolonged exposure may cause mutagenic effects.

Carcinogenic Effects

- May cause cancer.

Carcinogenic Effects		
	CAS	IARC
Ethylbenzene	100-41-4	Group 2B-Possible Carcinogen

Reproductive Effects

- May cause adverse reproductive effects - such as birth defects, miscarriages or infertility based on animal data.

Key to abbreviations

LC = Lethal Concentration MOD = Moderate
 LD = Lethal Dose TC = Toxic Concentration
 MLD = Mild

Section 12 - Ecological Information**12.1 Toxicity**

- Material data lacking.

12.2 Persistence and degradability

- Material data lacking.

12.3 Bioaccumulative potential

- Material data lacking.

12.4 Mobility in Soil

- Material data lacking.

12.5 Results of PBT and vPvB assessment

- No PBT and vPvB assessment has been conducted.

12.6 Other adverse effects

- No studies have been found.

Section 13 - Disposal Considerations**13.1 Waste treatment methods****Product waste**

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	UN1133	Adhesives	3	III	NDA
TDG	UN1133	ADHESIVES	3	III	NDA
IMO/IMDG	UN1133	ADHESIVES	3	III	NDA
ADN	UN1133	ADHESIVES	3	III	NDA
ADR/RID	UN1133	ADHESIVES	3	III	NDA
IATA/ICAO	UN1133	Adhesives	3	III	NDA

14.6 Special precautions for user

- None known.

14.7 Transport in bulk according to Annex II of

- Not relevant.

Marpol and the IBC Code

Section 15 - Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Acute, Chronic, Fire

State Right To Know				
Component	CAS	MA	NJ	PA
Ethylbenzene	100-41-4	Yes	Yes	Yes
Stoddard solvent	8052-41-3	Yes	Yes	Yes
Xylene	1330-20-7	Yes	Yes	Yes

Inventory						
Component	CAS	Canada DSL	Canada NDSL	EU EINECS	EU ELNICS	TSCA
Ethylbenzene	100-41-4	Yes	No	Yes	No	Yes
Stoddard solvent	8052-41-3	Yes	No	Yes	No	Yes
Xylene	1330-20-7	Yes	No	Yes	No	Yes

Canada

Labor

Canada - WHMIS - Classifications of Substances

• Ethylbenzene	100-41-4	B2, D2A, D2B
• Stoddard solvent	8052-41-3	B3, D2B
• Xylene	1330-20-7	B2, D2A, D2B

Canada - WHMIS - Ingredient Disclosure List

• Ethylbenzene	100-41-4	0.1 %
• Stoddard solvent	8052-41-3	1 %
• Xylene	1330-20-7	Not Listed

Environment

Canada - 2004 NPRI (National Pollutant Release Inventory)

• Ethylbenzene	100-41-4	Part 1, Group 1 Substance
• Stoddard solvent	8052-41-3	Part 5 Substance
• Xylene	1330-20-7	Part 1, Group 1 Substance; Part 5 Substance

Canada - 2005 NPRI (National Pollutant Release Inventory)

• Ethylbenzene	100-41-4	Part 1, Group 1 Substance
• Stoddard solvent	8052-41-3	Part 5 Substance
• Xylene	1330-20-7	Part 1, Group 1 Substance; Part 5 Substance

Canada - CEPA - Greenhouse Gases Subject to Mandatory Reporting

• Ethylbenzene	100-41-4	Not Listed
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	Not Listed

Canada - CEPA - Priority Substances List

• Ethylbenzene	100-41-4	Not Listed
----------------	----------	------------

• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	Priority Substance List 1 (substance not considered toxic)
Canada - DWQ (Drinking Water Quality) - IMACs		
• Ethylbenzene	100-41-4	Not Listed
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	Not Listed

Other		
Canada - Accelerated Reduction/Elimination of Toxics (ARET)		
• Ethylbenzene	100-41-4	Not Listed
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	Not Listed

Canada New Brunswick

Environment		
Canada - New Brunswick - Ozone Depleting Substances - Schedule A		
• Ethylbenzene	100-41-4	Not Listed
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	Not Listed
Canada - New Brunswick - Ozone Depleting Substances - Schedule B		
• Ethylbenzene	100-41-4	Not Listed
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	Not Listed

Europe

Other		
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification		
• Ethylbenzene	100-41-4	F; R11 Xn; R20
• Stoddard solvent	8052-41-3	Carc.Cat.2; R45 Muta.Cat.2; R46 Xn; R65
• Xylene	1330-20-7	R10 Xn; R20/21 Xi; R38
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits		
• Ethylbenzene	100-41-4	Not Listed
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	12.5%≤C: Xn; R:20/21
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling		
• Ethylbenzene	100-41-4	F Xn R:11-20 S:(2)-16-24/25-29
• Stoddard solvent	8052-41-3	T R:45-46-65 S:53-45
• Xylene	1330-20-7	Xn R:10-20/21-38 S:(2)-25
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Preparations		
• Ethylbenzene	100-41-4	Not Listed
• Stoddard solvent	8052-41-3	P
• Xylene	1330-20-7	C
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases		
• Ethylbenzene	100-41-4	S:(2)-16-24/25-29
• Stoddard solvent	8052-41-3	S:53-45

• Xylene	1330-20-7	S:(2)-25
----------	-----------	----------

United States

Labor

U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals

• Ethylbenzene	100-41-4	Not Listed
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	Not Listed

U.S. - OSHA - Specifically Regulated Chemicals

• Ethylbenzene	100-41-4	Not Listed
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	Not Listed

Environment

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

• Ethylbenzene	100-41-4	(listed under Ethyl benzene)
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	(isomers and mixtures)

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

• Ethylbenzene	100-41-4	1000 lb final RQ; 454 kg final RQ
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	100 lb final RQ; 45.4 kg final RQ

U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities

• Ethylbenzene	100-41-4	Not Listed
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

• Ethylbenzene	100-41-4	Not Listed
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

• Ethylbenzene	100-41-4	Not Listed
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	Not Listed

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

• Ethylbenzene	100-41-4	0.1 % de minimis concentration
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	1.0 % de minimis concentration

U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing

• Ethylbenzene	100-41-4	Not Listed
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	Not Listed

U.S. - RCRA (Resource Conservation & Recovery Act) - Basis for Listing - Appendix VII

• Ethylbenzene	100-41-4	Included in waste stream: F039
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	Included in waste stream: F039
U.S. - RCRA (Resource Conservation & Recovery Act) - Constituents for Detection Monitoring		
• Ethylbenzene	100-41-4	
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	
U.S. - RCRA (Resource Conservation & Recovery Act) - List for Hazardous Constituents		
• Ethylbenzene	100-41-4	
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	
U.S. - RCRA (Resource Conservation & Recovery Act) - Phase 4 LDR Rule - Universal Treatment Standards		
• Ethylbenzene	100-41-4	0.057 mg/L (wastewater); 10 mg/kg (nonwastewater)
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	0.32 mg/L (wastewater); 30 mg/kg (nonwastewater)
U.S. - RCRA (Resource Conservation & Recovery Act) - TSD Facilities Ground Water Monitoring		
• Ethylbenzene	100-41-4	
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	(total)
U.S. - RCRA (Resource Conservation & Recovery Act) - U Series Wastes - Acutely Toxic Wastes & Other Hazardous Characteristics		
• Ethylbenzene	100-41-4	Not Listed
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	waste number U239 (Ignitable waste)

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

• Ethylbenzene	100-41-4	carcinogen, initial date 6/11/04
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	Not Listed

U.S. - California - Proposition 65 - Developmental Toxicity

• Ethylbenzene	100-41-4	Not Listed
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	Not Listed

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

• Ethylbenzene	100-41-4	Not Listed
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	Not Listed

U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)

• Ethylbenzene	100-41-4	54 µg/day NSRL (inhalation); 41 µg/day NSRL (oral)
• Stoddard solvent	8052-41-3	Not Listed

• Xylene	1330-20-7	Not Listed
U.S. - California - Proposition 65 - Reproductive Toxicity - Female		
• Ethylbenzene	100-41-4	Not Listed
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	Not Listed
U.S. - California - Proposition 65 - Reproductive Toxicity - Male		
• Ethylbenzene	100-41-4	Not Listed
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	Not Listed

United States - Pennsylvania

Labor		
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List		
• Ethylbenzene	100-41-4	
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	
U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances		
• Ethylbenzene	100-41-4	Not Listed
• Stoddard solvent	8052-41-3	Not Listed
• Xylene	1330-20-7	Not Listed

15.2 Chemical Safety Assessment

- No Chemical Safety Assessment has been carried out.

15.3 Other Information

- WARNING: This product contains a chemical known to the State of California to cause cancer.

Section 16 - Other Information

Relevant Phrases (code & full text)

- H225 - Highly flammable liquid and vapour
- R11 - Highly flammable.
- R20 - Harmful by inhalation.

Revision Date

- 28/February/2018

Preparation Date

- 11/January/2012

Other Information

- Changes to this revision: Updated mailing address.

Disclaimer/Statement of Liability

- The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information, is accurate, complete or representative. Firestone Building Products Company, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons, if reasonable safety procedures are not followed. Additionally, Firestone Building Products Company assumes no responsibility for injury to buyer, the buyer's employees, or any third persons caused by abnormal use of this material, even if reasonable safety procedures are followed.

Key to abbreviations

NDA = No data available