

TECHNICAL INFORMATION SHEET

QuickSeam™ R.M.A. Strip

ITEM NUMBER: W56RAC1610

TIS #1414

Description:

QuickSeam R.M.A. Strip is a 10" (254.0 mm) wide RubberGard™ MAX membrane with two 3" (76.2 mm) wide strips of QuickSeam Tape factory laminated to it along its length.

It is used for roof membrane attachment beneath the RubberGard membrane as additional membrane securement as specified in Firestone Specifications and Details. QuickSeam R.M.A. is also used for membrane attachment in Firestone's RubberGard R.M.A. (Reinforced Mechanically Attached) System.



Method of Application:

1. Unroll the QuickSeam R.M.A. Strip with the release paper up.
2. Anchor the QuickSeam R.M.A. Strip using Firestone Seam Plates, V-Plates, or batten strips and fasteners 12" o.c. max. (305 mm) per current Firestone Specifications and Details.
3. Position RubberGard™ EPDM membrane over QuickSeam R.M.A. Strip with release paper in place and allow membrane to relax.
4. Fold back EPDM membrane to expose the R.M.A. Strip.
5. Prime the EPDM to be spliced to the tape using QuickPrime™ Plus and QuickScrubber™ or QuickScrubber Plus.
6. Use touch-push test to determine when the QuickPrime Plus is ready to be mated to the tape.
7. Remove the release paper.
8. Roll the primed EPDM membrane onto the tape.
9. Mate the membrane using a clean QuickScrubber Plus Handle and Pad, then roll the EPDM membrane over the QuickSeam R.M.A. Strip with a 1-1/2" (38.1 mm) wide silicone hand roller to ensure proper adhesion.
10. Refer to installation instructions for specifics: Technical Database, www.firestonebpco.com

Storage:

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (26.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.
- Shelf life of one year can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

Compliance:

Post Consumer Recycled Content: 0%
Pre Consumer Recycled Content: 0%
Manufacturing Location: Prescott, AR

Packaging:

Roll: 100' (30.5 m) roll, 1 roll per carton; 36 cartons per pallet

NOTE: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.

TECHNICAL INFORMATION SHEET



Physical Properties:	Value	Physical Properties:	Value
QuickSeam Tape:		RubberGard MAX:	
Base	Rubber Polymers	Base	EPDM
Color	Black	Color	Black
Solvents	None	Solvents	None
Solids	100%	Thickness	0.050" (1.26 mm) ± 20%
Specific Gravity	98± 0.02 (H ₂ O = 1)	Width	10" + 0, - 0.125"
Cured State	Cured		
Thickness	0.025" (0.63 mm) ± 0.007" (0.18 mm)		
Width	3" (133.3 mm) - 0, + 0.125"		

Please Contact your Firestone Roof Systems Advisor at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.