

TECHNICAL INFORMATION SHEET

QuickSeam™ II Professional Kit



Item Description
Seaming Kit

Item Number
W56RAC180L

Product Information

Description:

This professional grade seaming kit contains all the items necessary to complete 7.01 m (25.0') of seams for approved Firestone membranes. Included with the kit are step by step instructions on how to complete the seaming process.

Storage:

- Store in original unopened containers at temperatures between 15.6 - 26.7 °C (60 – 80 °F) until ready for use.
- When exposed to lower temperatures, restore to room temperature prior to use.
- Keep the material out of direct sunlight until ready for application.

Shelf Life:

- Shelf life of one (1) year can be expected if stored in original unopened container at temperatures between 15.6 - 26.7 °C (60 – 80 °F).
- Shelf life will be shortened if exposed to elevated temperatures.
- Rotate stock to insure stored material will not go beyond the shelf life of one (1) year.

Packaging:

The carton contains all items listed in the Product Data section.

Precautions:

- Review Safety Data Sheet (SDS) prior to use.
- Flammable. Keep away from fires (open flame) and other possible ignition sources during storage and use. Do not smoke when using.
- Red caution labels are required when shipping.
- Use only in well ventilated areas.
- Avoid contact with skin. Use of neoprene or nitrile gloves and eye protection with side shield is recommended.
- Use only in conjunction with QuickScrubber™ pad and handle. Do not apply with rollers, brushes or rags.
- Mix thoroughly before and during use.
- Thinning is not allowed.
- Keep out of reach of children.
- Dispose as a hazardous waste in accordance with local, state and federal regulations.
- Recommended cleaner is rubbing alcohol followed by soap and water.
- Do not contaminate with foreign materials.

QuickSeam™ II Professional Kit

LEED® Information:

Post Consumer Recycled Content: 0%
Post Industrial Recycled Content: 0%
Manufacturing Location: Prescott, AR

Product Data

<u>Property</u>	<u>Minimum Performance</u>
QuickSeam Cover Strip:	7.01 m of 152.4 mm (25.0' of 6.0") QuickSeam Cover Strip (See QuickSeam Cover Strip for more info)
Single-Ply LVOC Primer™	1 can (0.47 l, 1 pint) (See Single-Ply LVOC Primer for more info)
QuickScrubber Handle:	1 each
QuickScrubber Pad:	1 each
Seam Roller:	1 each
Special Crayon:	1 each
Instructions:	1 each

Please contact the Specialty Products Department at 1-888-264-1735 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.