

TECHNICAL INFORMATION SHEET

Single-Ply LVOC Splice Wash

Item Description

3 Gallon (11.4 L)

Item Number

W563587113



Product Information

Description:

Firestone Single-Ply LVOC Splice Wash is designed to clean and prepare Firestone single-ply membranes to be welded, or to receive Firestone Primers, Adhesives or Sealants, as noted in Firestone specifications and details.

Method of Application:

1. Surfaces to be welded, or to receive primer, adhesive or sealant shall be clean, dry, and free of foreign materials and excess dusting agent. Remove loose contaminates using brooms or rags.
2. Clean/prepare dirty surfaces using clean cotton rags wetted with Single-Ply LVOC Splice Wash, moving in circular motions with heavy pressure over affected areas. Membrane with caked dirt, including in-service thermoplastic membranes, should be scrubbed using QuickScrubber™ Handle & Pad wetted with Single-Ply Splice Wash LVOC, followed by wiping with clean rags to remove contaminates. On thermoplastic surfaces, the wipe with Single-Ply LVOC Splice Wash should be in one direction, flipping the rag often to avoid transferring contaminates.
3. Allow surfaces cleaned with Single-Ply Splice Wash LVOC to dry completely (usually within 10 to 30 minutes) before welding or applying primer, adhesive or sealant per current Firestone specifications and details.

Storage:

- Store in original unopened container, at temperatures between 60 °F (16 °C) and 80 °F (27 °C), away from all sources of direct heat and ignition, until ready for use. This is a flammable liquid.
- When exposed to lower temperatures, restore to room temperature prior to use.
- Keep the material out of direct sunlight until ready for immediate use.
- Although there is no shelf life for Single-Ply LVOC Splice Wash, it is best to rotate stock and use within one year.

Coverage Rate:

200-250 ft²/gallon (4.9 - 6.1 m²/L) on one side.

Precautions:

- Review Safety Data Sheet prior to use.
- Flammable liquid. Store and use away from all sources of direct heat and ignition.
- Cover tightly when not in use.
- Thinning is not permitted.
- Use of solvent-resistant neoprene gloves is required. Avoid contact with eyes and skin.
- Avoid breathing of vapors.
- Do not take internally.
- Cover container tightly when not in use.
- Use only in well ventilated areas.

TECHNICAL INFORMATION SHEET

Single-Ply LVOC Splice Wash

LEED® Information:

Post-Consumer Recycled Content: 0%
 Post Industrial Recycled Content: 0%
 Manufacturing Location: South Bend, IN
 *NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

Typical Properties	
Property	Value
Solvents	Solvent Blend of Acetone and Mineral Spirits
Viscosity	Very Thin, Free Flowing
Weight / Gallon	6.593 ± 0.329 lb/gal (790 ± 39.42 g/l)
VOC Content	Less than 250 g/l

Packaging Data	
Property	Value
Pail	3 gal (11.4 L)
Weight	Appx 20 lb (9 kg)

Please contact Firestone Technical Services Department at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications or other technical documents, subject to normal roof manufacturing tolerances. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.