

# TECHNICAL INFORMATION SHEET

## Coiled Metal Batten Strip



**Item Description**

3" (76.2 mm) o.c. pre-punched strips

**Item Number**

W56RAC3052

### Product Information

**Description:**

Coiled Metal Batten Strip is specifically designed to be used for anchoring Firestone membranes and flashing details as specified in Firestone Specifications and Details. Coiled Metal Batten Strip is packaged in a weather-resistant cardboard dispensing package which contains 220' (67 m) of batten strip. Using Coiled Metal Batten Strips in lieu of conventional pre-cut strips reduces labor and storage space. Coiled Metal Batten Strip has 3" (76.2 mm) o.c. pre-punched holes for greater flexibility in attaching to steel decks.

**Method of Application:**

Attach batten strips to the roof substrate or penetration using the appropriate Firestone fastener. Do not overdrive or underdrive fasteners. Start at one end of the batten strip and fasten towards the other to reduce bowing between fasteners.

**Storage:**

Store in original unopened containers protected from the weather.

**Packaging:**

220' (67 m) per coil, 52 coils per pallet

**Precautions:**

When cutting battens, round ends and remove burrs and sharp edges with a file.

**LEED® Information:**

Post-Consumer Recycled Content: 8%  
 Post Industrial Recycled Content: 17%  
 Manufacturing Location: Cleveland, OH  
 \*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.



### Typical Properties

| Property             | Value   |
|----------------------|---|
| Material             | Galvalume® AZ 55  |
| Corrosion Resistance | Meets FM No. 4470 criteria  |
| Length               | 220' (67 m) per coil  |
| Width                | 1" (25.4 mm)  |
| Thickness            | 0.04"/0.05" (1.13 mm/1.29 mm)   |
| Holes                | 0.34" (8.7 mm) diameter, at 3" (76.2 mm) o.c.<br>(Accommodates Firestone All-Purpose, Heavy-Duty, Heavy-Duty Plus and Concrete Drive Fasteners) |
| Weight               | 32 lb (14.5 kg) per coil  |

Galvalume® is a registered trademark of BIEC International, Inc.

Please contact Firestone Technical Services at 1-800-428-4511 for further information.

*This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications or other technical documents, subject to normal roof manufacturing tolerances. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.*