

TECHNICAL INFORMATION SHEET

Pourable Sealer S-10 (Part A & Part B)

Item Description

Part A: One gallon (3.78 L) Can
Part B: One pint (0.47 L) Can

Item Number

W563587065



Product Information

Description:

Pourable Sealer S-10 is designed for sealing penetration pockets used in conjunction with Firestone roof systems.

Product Packaging

Part A:	One gallon (3.78 L) can
Part B:	One pint (0.47 L) can
Carton:	4 one-gallon cans and 4 one-pint cans
Weight per Carton:	Approximately 46 lb (21 kg)

Method of Application:

1. Substrates must be free of water, dust, dirt, oil, and any other contaminants.
2. After preparation of the penetration pocket per Firestone details, pour Part B into Part A, and mix thoroughly with a drill with a mixing blade. Mix until the Part A material is uniform in color. If material contains gray streaks, mixing should continue. Mix so that material on the bottom and sides of the can is fully circulated and blended.
3. Pour the Pourable Sealer into the penetration pocket. Mound the sealer so as to shed water away from the actual penetration.
4. Do not thin Pourable Sealer S-10 or use partial quantities.

Storage:

- Store in original, unopened containers, at temperatures between 60 °F and 80 °F (15.6 °C and 26.7 °C) until ready for use.
- When exposed to lower temperatures, restore to room temperature prior to use.
- For optimum results, rotate stock to ensure stored material has not exceeded the shelf life of one (1) year.

Shelf Life:

- Shelf life of one (1) year can be expected when stored in original sealed containers at temperatures between 60 °F and 80 °F (15.6 °C and 26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

Coverage Rate:

Coverage rate of 200 in³ (3277 cm³) for each mixture of Part A and Part B can be expected.

TECHNICAL INFORMATION SHEET

Pourable Sealer S-10 (Part A & Part B)

Precautions:

- Review Safety Data Sheet (SDS) prior to use.
- **Avoid moisture contamination. Contact with water can generate explosive pressure in a closed container.**
- Do not thin.
- Do not contaminate with foreign materials.
- Avoid contact with skin. Pourable Sealer S-10 is extremely difficult to remove. Disposable gloves are recommended when mixing and dispensing pourable sealer.
- Avoid breathing vapors. Use only in well ventilated areas.
- Cover containers tightly when not in use.

LEED® Information:

Post Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: South Bend, IN

*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

Typical Properties

<u>Property</u>	<u>Typical Performance</u>
Base:	Polyurethane
Color:	Mixed: Black Part A: Light Gray Part B: Black
Solvents:	None
Solids:	100%
Viscosity:	Part A: 250,000 to 325,000 cps w/ Brookfield #7 spindle at 4 RPM Part B: Thin, Free Flowing
Specific Gravity:	Part A: 1.25 Part B: 1.14
Weight/Gallon:	Part A: 10.40 lb/gal (1.25 kg/L) Part B: 9.50 lb/gal (1.14 kg/L)
Mix Ratio:	1 can of Part B to 1 can of Part A
Pot Life:	30 minutes (max.) at 72 °F (22.2 °C)
V.O.C. Content:	0 g/L

Please contact Firestone Technical Services Department at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.