

# TECHNICAL INFORMATION SHEET

## UltraPly™ TPO Universal Pipe Boot



**Item Description**

White  
Tan  
Gray

**Item Number**

W56TPO301U  
W56TPO01U  
W56TPOG01U

### Product Information

**Description:**

The UltraPly TPO Universal Pipe Boot is specifically designed for the flashing of round penetrations on TPO installations. The UltraPly TPO Universal Pipe Boot fits various penetrations from 1" (25 mm) to 6" (150 mm). It must be cut to correct size before installation.

**Method of Application:**

1. UltraPly TPO membrane shall be clear of all dust, dirt and other contaminants prior to installation of the UltraPly TPO Universal Pipe Boot.
2. Penetration shall be clean of foreign material and any old flashing materials.
3. Cut out a circle, above the rib, on the outside of a level ring of the UltraPly TPO Universal Pipe Boot that is smaller than the penetration.
4. Heat-weld the flashing into place and install the clamp and sealant per current UltraPly TPO specifications.

**Storage:**

Store material in its original unopened packaging away from sources of physical damage or chemical contamination.

**Precautions:**

Do not install over uneven substrates.

**LEED® Information:**

Post-Consumer Recycled Content: 0%  
Post Industrial Recycled Content: 0%  
Manufacturing Location: Wellford, SC

\*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

Typical Properties	
Property	Value
Material	Thermoplastic Polyolefin (TPO)
Color	White, Tan, Gray
Clamp	Stainless steel – worm gear type
Pipe Flange	13" (330 mm) diameter
Thickness	0.055"– 0.075" (1.4 mm – 1.9 mm)

Fits the Pipe Outside Diameter	
1"	25 mm
1½"	38 mm
2"	50 mm
3"	76 mm
4"	102 mm
5"	127 mm
6"	152 mm

Product Packaging	
Units per Carton	10 UltraPly TPO Universal Pipe Boots - 10 Stainless Steel Clamps

Please contact Firestone Technical Services Department at 1-800-428-4511 for further information.

*This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications or other technical documents, subject to normal roof manufacturing tolerances. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.*