

TECHNICAL INFORMATION SHEET

UltraPly™ QuickSeam™ R.M.A. Strip

Item Description
100' (30.5 m) Roll

Item Number
W56TPO30T0



Product Information

Description:

UltraPly QuickSeam R.M.A. Strip is a 10" (254.0 mm) wide UltraPly TPO membrane with two 3" (76.2 mm) wide strips of tape factory laminated to it along its length. It is used for roof membrane attachment beneath the UltraPly TPO membrane as additional membrane securement as specified in Firestone specifications and details.

Method of Roofing Attachment Application:

1. Unroll the UltraPly QuickSeam R.M.A. Strip with the release paper up.
2. Anchor the QuickSeam R.M.A. Strip using Firestone Heavy Duty Seam Plates and Firestone HD Fasteners 12" (305 mm) o.c. per current Firestone specifications and details.
3. Position UltraPly TPO membrane over UltraPly QuickSeam R.M.A. Strip with release paper in place and allow membrane to relax.
4. Fold back UltraPly TPO membrane to expose the R.M.A. Strip.
5. Prime the UltraPly TPO in the area to be spliced to the tape using Single-Ply QuickPrime™ Primer or Single-Ply LVOC Primer, applied with QuickScrubber™ or QuickScrubber Plus pad and handle.
6. Use touch-push test to determine when primer is dry and ready to be mated to the tape on the RMA Strip.
7. Remove the release paper from the tape.
8. Roll the primed UltraPly TPO membrane onto the tape.
9. Mate the membrane using a clean QuickScrubber Plus Handle and Pad, then roll the UltraPly TPO membrane over the UltraPly QuickSeam R.M.A. Strip with a 1½" (38.1 mm) wide silicone hand roller to ensure proper adhesion.
10. Additional information available at Firestone's Technical Database, www.firestonebpc.com.

Storage:

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 100 °F (26.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.

Shelf Life:

- Shelf life of two years can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

Precautions:

- Do not use UltraPly QuickSeam R.M.A. Strip with UltraPly TPO XR membranes
- Refer to Safety Data Sheet (SDS) for more information.

TECHNICAL INFORMATION SHEET

UltraPly™ QuickSeam™ R.M.A. Strip

LEED® Information:

Post-Consumer Recycled Content: 0%
 Post Industrial Recycled Content: 0%
 Manufacturing Location: Michigan Center, MI
 *NOTE: LEED® is a registered trademark of the U.S. Green Building Council.



Packaging	
Property	Value
Roll	100' (30.5 m) roll
Carton	1 roll per carton

NOTE: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.

Typical Properties

QuickSeam Tape		Membrane	
Property	Value	Property	Value
Base	Rubber Polymers	Base	TPO
Color	White	Color	White
Solvents	None	Solvents	None
Solids	100%	Thickness	0.050" (1.26 mm) ± 20%
Specific Gravity	98 ± 0.02 (H ₂ O =1)	Width	10" + 0, -0.125" (254.0 mm) +0, -3.2 mm)
Cured State	Cured		
Thickness	0.030" (0.76 mm) ± 0.005" (0.127 mm)	NOTE: Refer to Technical Information Sheet for UltraPly TPO for additional information.	
Width	3" (76.2 mm) -0, + 0.1.25" mm		

Please contact Firestone Technical Services at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications or other technical documents, subject to normal roof manufacturing tolerances. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.