

# TECHNICAL INFORMATION SHEET

## UltraPly™ TPO QuickSeam™ 9½" Flashing

**Description**

White  
Gray  
Tan

**Item Number**

W56TPO30T9  
W56TPOG0T9  
W56TPO0T9

### Product Information

**Description:**

UltraPly TPO QuickSeam 9½" (241 mm) Flashing is an unsupported (non-reinforced) TPO membrane factory laminated to white seam tape. UltraPly TPO QuickSeam 9½" (241 mm) Flashing is used to flash gravel stops and other flashing applications as indicated in Firestone specifications and details.

**Method of Application:**

1. Use Firestone Single-Ply QuickPrime™ Primer or Single-Ply LVOC Primer applied with a QuickScrubber™ or QuickScrubber Plus pad and handle to clean and prime membrane and metal mating surfaces to receive UltraPly QuickSeam 9½" (241 mm) Flashing.
2. Refer to current Firestone specifications for application instructions and details using Firestone UltraPly TPO QuickSeam 9½" (241 mm): [www.firestonebpc.com](http://www.firestonebpc.com)

**NOTE:** UltraPly TPO QuickSeam products must be heat-formed to conform to seam step-offs, metal laps, angle changes, etc.

**Storage:**

- Store in original unopened containers indoors at temperatures between 60 °F (16 °C) and 80 °F (27 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (27 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.
- Shelf life of 1.5 years can be expected when stored in original container at temperatures between 60 °F (16 °C) and 80 °F (27 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

**Precautions:**

Refer to Safety Data Sheet (SDS).

**LEED® Information:**

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Michigan Center, MI

\*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.



# TECHNICAL INFORMATION SHEET

## UltraPly™ TPO QuickSeam™ 9½" Flashing

### Packaging

Property	Value
Roll	9½" (241 mm) x 100' (30.5 m) roll
Carton	1 roll per carton

**NOTE:** QuickScrubber and/or QuickScrubber Plus Pads and Handles are included in each carton. Quantities vary depending on the QuickSeam product.

### Typical Properties

QUICKSEAM TAPE		TPO UNSUPPORTED FLASHING	
Property	Value	Property	Value
Base	Rubber Polymers	Base	TPO
Color	White	Color	White, Gray, Tan
Percent Solids	100%	Solvents	None
Specific Gravity	1.08 ± 0.03	Percent Solids	100%
Cured State	Cured	Specific Gravity	0.96 ± 0.02
Thickness	0.030" (0.76 mm) ± .005" (0.13 mm)	Thickness	0.030" (0.76 mm) ± 10%
Width	9¾" (248 mm) - 0 /+ 1/16" (1.6 mm)	Width	9½" (241 mm) + 0 / - ⅛" (3.2 mm)
Length	100' (30.5 m)	Length	100' (30.5 m)

Please contact Firestone Technical Services Department at 1-800-428-4511 for further information.

*This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications or other technical documents, subject to normal roof manufacturing tolerances. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.*